

# Prince Street House and Home

## Lexington

High Performance™

PRODUCT NUMBER: 4LX50R6301  
STANDARD COLORLINE: 36  
YARN SYSTEM: Tactesse(r) nylon  
DYE METHOD: Piece Dye  
SOIL/STAIN PROTECTION: Invista STAINMASTER® Grand Luxura® Soil Resistant Treatment

### PRODUCT SPECIFICATIONS

#### U.S.

#### METRIC

TUFTED YARN WEIGHT:	50 oz/yd <sup>2</sup>	1695.0 g/m <sup>2</sup>
MACHINE GAUGE:	1/8 in	31.5 ends/10 cm
STITCHES:	10 /in	39.37 ends/10 cm
SIZE:	12 ft 6 in	3.810 m
PATTERN REPEAT:	1" W x 1-1/8" L	

### PERFORMANCE SPECIFICATIONS

Radiant Panel: Passes Class 1 (ASTM-E648) Critical Radiant Flux  $\geq 0.45$  W/cm<sup>2</sup> - Direct Glue  
Smoke Density: DM Corrected < 450 (ASTM-E662)  $\leq 450$  (ASTM E - 662)  
Static: (AATCC - 134) < 3.5 KV  
Flammability: Passes Methenamine Pill Test (DOC-FF1-70)  
Standard Backing: High Performance™(3.810 m)  
Backing Options: High Performance™(3.810 m)

### ADDITIONAL INFORMATION :

Warranty / Wear Performance: Please inquire about product warranties for specific backing options.

Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation.

\* The shearing process may result in a small loss of yarn weight.

Product Specifications are derived from measurements subject to normal manufacturing tolerances and may be changed without prior notice as long as performance is not affected.

Issue Date:12/6/04 ts