

Prince Street House and Home

Ludlow

High Performance™

PRODUCT NUMBER: 4LW38R6301
STANDARD COLORLINE: 72
YARN SYSTEM: 100% Wear-Dated® nylon
DYE METHOD: Piece Dye
SOIL PROTECTION: Wear-Dated® Approved Soil Protection

PRODUCT SPECIFICATIONS

	U.S.	METRIC
TUFTED YARN WEIGHT:	38 oz/yd ²	1288.0 g/m ²
MACHINE GAUGE:	1/10 in	39.4 ends/10 cm
PILE HEIGHT:	0.255 in	6.5 mm
STITCHES:	10 /in	39.37 ends/10 cm
PILE DENSITY:	9523	
TOTAL THICKNESS:	0.340 in	8.6 mm
SIZE:	12 ft 6 in	3.810 m
PATTERN REPEAT:	75-13/64 in (w) Stripe	

PERFORMANCE SPECIFICATIONS

Radiant Panel: Passes Class 1 (ASTM-E648) Critical Radiant Flux ≥ 0.45 W/cm² - Direct Glue
Smoke Density: DM Corrected < 450 (ASTM-E662) ≤ 450 (ASTM E - 662)
Static: (AATCC - 134) < 3.5 KV
Flammability: Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing: High Performance™(3.810 m)
Backing Options: High Performance™(3.810 m)

ADDITIONAL INFORMATION :

Warranty / Wear Performance: Please inquire about product warranties for specific backing options.

Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation.

* The shearing process may result in a small loss of yarn weight.

Product Specifications are derived from measurements subject to normal manufacturing tolerances and may be changed without prior notice as long as performance is not affected.

Issue Date:6/23/04 ts