

Prince Street House and Home

Spring

High Performance™

PRODUCT NUMBER: 4SP46R6201
STANDARD COLORLINE: 72
YARN SYSTEM: Invista Type 6,6 Nylon
DYE METHOD: Piece Dye
SOIL PROTECTION: Invista STAINMASTER® Grand Luxura® Soil Resistant Treatment

PRODUCT SPECIFICATIONS	U.S.	METRIC
TUFTED YARN WEIGHT:	46 oz/yd ²	1560.0 g/m ²
MACHINE GAUGE:	3/16 in	21 ends/10 cm
PILE HEIGHT:		
- High:	0.317 in	8.1 mm
- Low:	0.217 in	5.5 mm
STITCHES:	11.5 /in	45.28 ends/10 cm
PILE DENSITY:	7200	
TOTAL THICKNESS:	0.370 in	9.4 mm
SIZE:	12 ft 6 in	
PATTERN REPEAT:	18 in W x 33 in L	45.7200 cm W x 83.8200 cm L

PERFORMANCE SPECIFICATIONS

Radiant Panel: Passes Class 1 (ASTM-E648) Critical Radiant Flux ≥ 0.45 W/cm² - Direct Glue
Smoke Density: DM Corrected < 450 (ASTM-E662) ≤ 450 (ASTM E - 662)
Static: < 3.5 kV (AATCC-134)
Flammability: Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing: High Performance™
Backing Options: High Performance™()

ADDITIONAL INFORMATION :

Warranty / Wear Performance: Please inquire about Residential warranties.

Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation.

Product Specifications are derived from measurements subject to normal manufacturing tolerances and may be changed without prior notice as long as performance is not affected.

Issue Date:1/23/03 ts